



NOTES:

1. MATERIAL: TPE
OTHER MATERIALS AVAILABLE
2. MEETS IEC 60601 FOR PIN SETBACK, 0.039" [1MM]
3. GENERAL PERFORMANCE (CONTACT POI FOR TEST CONDITIONS)
LIFE CYCLE: 1000+ INSERTION CYCLES
MAX. CURRENT: 8 AMPS
4. OPERATING TEMPERATURE: +5° C TO +60° C
5. UL94 HB
6. MEETS DIN 42-802
7. EXTRACTION FORCE: SEE MATING JACK FOR PERFORMANCE DATA

<table border="1"> <tr> <td>C</td> <td>REV PER ECO 39621 NPG 12/8/22</td> <td>12/20/22</td> <td>SWA</td> </tr> <tr> <td>B</td> <td>RER PER ECO 9467 JAP 4/21/2006</td> <td>5/24/06</td> <td>JAP</td> </tr> <tr> <td>A</td> <td>REL FOR PROD ECO 851 BB 9/20/94</td> <td>9/21/94</td> <td>LL</td> </tr> <tr> <td>REV</td> <td>DESCRIPTION</td> <td>DATE</td> <td>BY</td> </tr> </table>			C	REV PER ECO 39621 NPG 12/8/22	12/20/22	SWA	B	RER PER ECO 9467 JAP 4/21/2006	5/24/06	JAP	A	REL FOR PROD ECO 851 BB 9/20/94	9/21/94	LL	REV	DESCRIPTION	DATE	BY	<p>TOLERANCES UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES DIMENSIONS IN [] METRIC</p> <p>FRACTIONAL ±1/64</p> <p>DECIMAL .00 ±.01 [.25mm] .000 ±.005 [.127mm]</p> <p>ANGULAR ±.5°</p>		<p>APPROVALS</p> <p>DRAWN BRINDLE</p> <p>CHECKED <i>J. Lehar</i></p> <p>PROJ ENGR</p> <p>APPROVED <i>J. Lehar</i></p> <p>PROJECT 1449</p>		<p>DATE</p> <p>5/24/94</p> <p>12/14/22</p> <p>12/14/22</p> <p>FSCM</p>		<p>P Technologies BECAUSE EVERYTHING CONNECTS</p> <p>6591 Merriman Road, Roanoke, VA 24018 Phone: 540-772-7950 Fax: 540-989-7519</p>	
C	REV PER ECO 39621 NPG 12/8/22	12/20/22	SWA																							
B	RER PER ECO 9467 JAP 4/21/2006	5/24/06	JAP																							
A	REL FOR PROD ECO 851 BB 9/20/94	9/21/94	LL																							
REV	DESCRIPTION	DATE	BY																							
<p>REVISIONS</p> <p>THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND MAY NOT BE ISSUED OR REPRODUCED, IN WHOLE, OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF P1 TECHNOLOGIES.</p>				<p>TITLE CONNECTOR, 441 1.5mm TOUCH PROOF</p> <p>SCALE 4:1</p>		<p>SIZE DWG A 36003-50</p>		<p>REV SHT C 1 OF 1</p>																		