



NOTES:

1. MATERIAL: PBT
OTHER MATERIALS AVAILABLE
2. SIGNAL CONTACT PLATING: SOFT NICKEL, THEN SOFT GOLD
3. PIN SETBACK: 0.10" [2.5MM]
EN 60601 TOUCHPROOF
4. GENERAL PERFORMANCE (CONTACT PIT FOR TEST CONDITIONS)
EXTRACTION FORCE: 3.7 LBS AVERAGE (16.5N)
LIFE CYCLE: 1000+ INSERTION CYCLES
MAX. CURRENT: 11 AMPS
5. OPERATING TEMPERATURE: +5°C TO +60°C
6. UL94 V-0/5V
7. DIN 802 COMPLIANT

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND MAY NOT BE ISSUED OR REPRODUCED, IN WHOLE, OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF P1 TECHNOLOGIES.

REV	DESCRIPTION	DATE	APPVD
D	REV PER ECO 27944 KDS 10/11/16	10/18/16	SLH
C	REV PER ECO 26711 T AS 3/23/16	3/29/16	KE
	REDRAWN IN SOLIDWORKS XZ 10/14/15		
B	REV PER ECO 3390 GSOX 2/24/98	3/4/98	GSOX
A	REL PER ECO 3109 RS 10/13/97	10/13/97	RS
REVISIONS			

TOLERANCES
UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES DIMENSIONS IN [] METRIC
FRACTIONAL ±1/64
DECIMAL .00 ±.01 [.25mm] .000 ±.005 [.127mm]
ANGULAR ±.5°

APPROVALS	DATE
DRAWN SINCLAIR	9/16/97
CHECKED WDS	7/5/00
PROJ ENGR SINCLAIR	9/16/97
APPROVED <i>[Signature]</i>	7/10/2020
PROJECT 6942	FSCM

 6591 Merriman Road, Roanoke, VA 24018 Phone: 540-772-7950 Fax: 540-989-7519		TITLE JACK, PANEL MOUNT, Ø1.5mm	
		SCALE 5/1	
SIZE B	DWG 37913-50	REV D	SHT 1 OF 1

D
C
B
A