



- NOTES:**
1. MATERIAL: ABS
OTHER MATERIALS AVAILABLE
 2. SIGNAL CONTACT PLATING: SOFT NICKEL, THEN SOFT GOLD
 3. PIN SETBACK: 0.08" [2.1MM]
EN 60601 TOUCHPROOF
 4. GENERAL PERFORMANCE (CONTACT P1T FOR TEST CONDITIONS)
EXTRACTION FORCE: .87 LB AVERAGE (3.9 N)
LIFE CYCLE: 1000+ INSERTION CYCLES
HIPOT: 1000 VAC between contacts
MAX. CURRENT: 8 AMPS
 5. UL94 HB
 6. WAVE SOLDERABLE
 7. MATES WITH 44-SERIES & 444 PLUGS

REV	DESCRIPTION	DATE	BY
D	REV PER ECO 28666 XZ 2/17/17	3/28/17	SLH
C	REV PER ECO 26154 KDS 1/6/16 REDRAWN IN SOLIDWORKS	1/12/16	JAB
B	REL PER ECO 3233 SJ 12/15/97	12/17/97	SJ
A	REL PER ECO 3155 SJ 11/5/97	9/3/97	SJ
REVISIONS			

TOLERANCES UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES DIMENSIONS IN [] METRIC		APPROVALS	DATE
FRACTIONAL $\pm 1/64$	DECIMAL .00 \pm .01 [.25mm] .000 \pm .005 [.127mm]	DRAWN S. JAMISON	11/5/97
		CHECKED WMS	7/5/20
ANGULAR $\pm 5^\circ$	APPROVED [Signature]	PROJ ENGR	
		PROJ ENGR 6938	FSCM

P Technologies
BECAUSE EVERYTHING CONNECTS

6591 Merriman Road, Roanoke, VA 24018
Phone: 540-772-7950 Fax: 540-989-7519

TITLE JACK, 37929 1.0MM, 3 PIN

SCALE 4:1

SIZE B	DWG 37929-50	REV D	SHT 1 OF 1
--------	--------------	-------	------------

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND MAY NOT BE ISSUED OR REPRODUCED, IN WHOLE, OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF P1 TECHNOLOGIES.