



- △ NOTES:
1. MATERIAL: PBT
OTHER MATERIALS AVAILABLE
 2. SIGNAL CONTACT PLATING: SOFT NICKEL, THEN SOFT GOLD
 3. PIN SETBACK: 0.07" [1.8MM]
EN 60601 TOUCHPROOF
 4. GENERAL PERFORMANCE (CONTACT PIT FOR TEST CONDITIONS)
EXTRACTION FORCE: 1.1 LBS MINIMUM (4.9N)
LIFE CYCLE: 1000+ INSERTION CYCLES
HIPOT: 1000 VAC between contacts
5000 VDC TO ANY EXPOSED METAL COMPONENTS
MAX. CURRENT: 8 AMPS
 5. OPERATING TEMPERATURE: +5° C to + 60° C
 6. UL94 V-0/5V
 7. WAVE SOLDERABLE
 8. MATES WITH 44-SERIES & 444 PLUGS

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND MAY NOT BE ISSUED OR REPRODUCED, IN WHOLE, OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF P1 TECHNOLOGIES.

REV	DESCRIPTION	DATE	APPVD
C	REV PER ECO 28666 XZ 2/17/17	3/28/17	SLH
B	REV PER ECO 8484 GSOX 1/26/05	3/30/05	GS
A	REL PER ECO 4241 XZ 4/30/99	5/3/99	XZ
REVISIONS			

TOLERANCES		APPROVALS	DATE	 6591 Merriman Road, Roanoke, VA 24018 Phone: 540-772-7950 Fax: 540-989-7519
UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES DIMENSIONS IN [] METRIC		DRAWN XZHOU	4/30/99	
FRACTIONAL ±1/64		APPROVED <i>[Signature]</i>	7/9/2020	TITLE JACK, 3 PIN, .040 TRIANGULAR NO STANDOFFS SCALE 5/1
DECIMAL .00 ±.01 [.25mm] .000 ±.005 [.127mm]		PROJ ENGR		
ANGULAR ±.5°		APPROVED <i>[Signature]</i>	7/9/2020	SIZE DWG B 38253-50
		PROJECT 7108	FSCM	