



NOTES:

1. MATERIAL: PBT
OTHER MATERIALS AVAILABLE
2. SIGNAL CONTACT PLATING: SOFT NICKEL, THEN SOFT GOLD
3. PIN SETBACK: 0.14" (3.6mm)
EN 60601 TOUCHPROOF
4. GENERAL PERFORMANCE (CONTACT POI FOR TEST CONDITIONS)
EXTRACTION FORCE: 2.2 LBS AVERAGE (9.7 N)
LIFE CYCLE: 1000+ INSERTION CYCLES
HIPOT: 1000 VAC BETWEEN CONTACTS
MAX. CURRENT: 8 AMPS
5. OPERATING TEMPERATURE: +5° C to + 60° C
6. UL94 V-0/5V
7. WAVE SOLDERABLE

REV	DESCRIPTION	DATE	BY
D	REV PER ECO 35561 TAS 1/27/20	1/29/20	US
C	REV PER ECO 9515 XZ 4/5/06	4/5/06	XZ
B	REV PER ECO 8092 GSOX 12/21/04	12/27/04	GS
A	RELEASE PER ECO 4645 GSOX 11/18/04	3/15/00	GS
REVISIONS			

TOLERANCES UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES DIMENSIONS IN [] METRIC		APPROVALS DRAWN GSOX	DATE 11/11/04	Technologies <small>BECAUSE EVERYTHING CONNECTS</small> 6591 Merriman Road, Roanoke, VA 24018 Phone: 540-772-7950 Fax: 540-989-7519
FRACTIONAL ±1/64 DECIMAL .00 ±.01 [.25mm] .000 ±.005 [.127mm]		CHECKED <i>K. Spauldy</i> PROD ENGR	DATE 1/28/2020	
ANGULAR ±.5°		APPROVED <i>K. Spauldy</i> PROJECT	DATE 1/28/2020 FSCM	TITLE JACK, 1MM 4PIN
		7132	SCALE 4:1	SIZE DWG B 38319-50
				REV D SHT 1 OF 1

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND MAY NOT BE ISSUED OR REPRODUCED, IN WHOLE, OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF P1 TECHNOLOGIES.

D
C
B
A