


NOTES:

1. MATERIAL: PBT
OTHER MATERIALS AVAILABLE
2. SIGNAL CONTACT PLATING: SOFT NICKEL, THEN SOFT GOLD
3. PIN SETBACK: 0.23" (5.8 mm)
EN 60601 TOUCHPROOF
4. GENERAL PERFORMANCE (CONTACT P1T FOR TEST CONDITIONS)
EXTRACTION FORCE: 3.7 lbs (16.5 N) Average
LIFE CYCLE: 1000+ INSERTION CYCLES
MAX. CURRENT: 8 AMPS
5. OPERATING TEMPERATURE: +5° C to +60° C
6. UL94 V-0/5V
7. WAVE SOLDERABLE
8. MATES WITH 255
9. Max Flash .003"

				<p>TOLERANCES UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES DIMENSIONS IN [] METRIC</p>		<p>APPROVALS</p>		<p>DATE</p>		 <p>P Technologies BECAUSE EVERYTHING CONNECTS</p> <p>6591 Merriman Road, Roanoke, VA 24018 Phone: 540-772-7950 Fax: 540-989-7519</p>	
				<p>FRACTIONAL ±1/64</p>		<p>DRAWN S Heckman</p>		<p>6/16/18</p>			
				<p>DECIMAL .00 ±.01 [.25mm] .000 ±.005 [.127mm]</p>		<p>CHECKED T. Stump</p>		<p>7/8/20</p>			
				<p>ANGULAR ±.5°</p>		<p>PROJ ENGR</p>				<p>TITLE JACK FEMALE, 2MM, PANEL MOUNT</p>	
<p>REVISIONS</p>						<p>APPROVED K. Spauldy</p>		<p>7/10/2020</p>		<p>SCALE 1:1</p>	
<p>THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND MAY NOT BE ISSUED OR REPRODUCED IN WHOLE, OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF P1 TECHNOLOGIES.</p>						<p>PROJECT</p>		<p>FSCM</p>		<p>SIZE DWG A 43008-50</p>	
						<p>REV A</p>		<p>SHT OF 1</p>			