



NOTES:

1. MATERIAL: PBT
OTHER MATERIALS AVAILABLE
2. SIGNAL CONTACT PLATING: SOFT NICKEL, THEN SOFT GOLD
3. PIN SETBACK: 0.07" [1.8MM]
EN 60601 TOUCHPROOF
4. GENERAL PERFORMANCE (CONTACT P1T FOR TEST CONDITIONS)
EXTRACTION FORCE: 1.1 LBS MINIMUM (4.9N)
LIFE CYCLE: 1000+ INSERTION CYCLES
HIPOT: 1000 VAC BETWEEN CONTACTS
5000 VDC TO ANY EXPOSED METAL COMPONENTS
MAX. CURRENT: 8 AMPS
5. OPERATING TEMPERATURE: +5° C TO + 60° C
6. UL94 V-0/5V
7. WAVE SOLDERABLE
8. MATES WITH 44-SERIES & 444 PLUGS

TOLERANCES UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES DIMENSIONS IN [] METRIC		APPROVALS	DATE	<p>6591 Merriman Road, Roanoke, VA 24018 Phone: 540-772-7950 Fax: 540-989-7519</p>
FRACTIONAL ±1/64	DRAWN T. HOFFMAN	8/23/23	TITLE JACK, 3 PIN, .040 TRIANGULAR 2 STANDOFFS .062 TALL	
DECIMAL .00 ±.01 [.25mm] .000 ±.005 [.127mm]	CHECKED MAB	9/6/23	SCALE 5:1	
ANGULAR ±.5°	PROJ ENGR		SIZE DWG B 44046-50	
APPROVED J. REHAK		9/7/23	REV A	SHT 1 OF 1
PROJECT		FSCM		

A	RELEASE PER ECO 40575 TAH 8/23/23	9/19/23	JDB
REV.	DESCRIPTION	DATE	BY
REVISIONS			

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND MAY NOT BE ISSUED OR REPRODUCED, IN WHOLE, OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF P1 TECHNOLOGIES.