



NOTES:

- 1. MATERIAL: PBT
OTHER MATERIALS AVAILABLE
- 2. SIGNAL CONTACT PLATING: SOFT NICKEL, THEN SOFT GOLD
- 3. PIN SETBACK: 0.07" [1.8 MM]
EN 60601 TOUCHPROOF
- 4. GENERAL PERFORMANCE (CONTACT P1T FOR TEST CONDITIONS)
EXTRACTION FORCE: 1.1 LBS MINIMUM (4.9N)
LIFE CYCLE: 1000+ INSERTION CYCLES
HIPOT: 1000 VAC BETWEEN CONTACTS
5000 VDC TO ANY EXPOSED METAL COMPONENTS
MAX. CURRENT: 8 AMPS
- 5. OPERATING TEMPERATURE: +5° C TO + 60° C
- 6. UL94 V-0/5V
- 7. WAVE SOLDERABLE
- 8. MATES WITH 44-SERIES & 444 PLUGS

TOLERANCES UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES DIMENSIONS IN [] METRIC	APPROVALS	DATE	 Technologies <small>BECAUSE EVERYTHING CONNECTS</small> 6591 Merriman Road, Roanoke, VA 24018 Phone: 540-772-7950 Fax: 540-989-7519
	DRAWN T. HOFFMAN	5/23/23	
	CHECKED MAB	9/6/23	
	PROJ ENGR		
FRACTIONAL $\pm 1/64$	APPROVED J. REHAK	9/7/23	TITLE JACK, 3 PIN, .040 TRIANGULAR 6 STANDOFFS .020 TALL
DECIMAL .00 $\pm .01$ [.25mm] .000 $\pm .005$ [.127mm]	PROJECT	FSCM	SCALE 5:1
ANGULAR $\pm .5^\circ$			SIZE DWG B 44048-50
			REV A SHT 1 OF 1

A	RELEASE PER ECO 40575 TAH 8/23/23	9/19/23	JDB
REV.	DESCRIPTION	DATE	BY
REVISIONS			

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND MAY NOT BE ISSUED OR REPRODUCED, IN WHOLE, OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF P1 TECHNOLOGIES.